

Submittal Data Information

301-1044

SCX Series Centrifugal Pump

Effective: May 31, 2012 Supersedes: April 17, 2012

Job: Engi	: Engineer:		Contractor:			Rep:			
ITEM NO.	MODEL NO.	IMP. DIA.	G.P.M.	HEAD/FT.	H.P.	ELEC. CHAR.			

Features

Compact Design: Close-Coupled design saves space and simplifies maintenance and installation.

Superior Materials of Construction: Complete AISI 304 Stainless Steel housing for corrosion resistance, smooth flow path, quality appearance, and improved strength and ductility.

Installation Flexibility: Can be mounted horizontally or vertically.

High efficiency Impeller:

Enclosed impelier of precision molded Noryl with ultra-smooth flow ports maximizes performance and efficiency.

Mechanical Seal: Standard carbon on ceramic seal faces with Viton elastomers. Optional seal faces and elastomers are available to handle a variety of working fluids.

Motors: Rugged ball bearing design NEMA standard open drip proof or totally enclosed, fan cooled motors are available for continuous duty under all operating conditions.


Drain/Vent Ports: Stainless steel vent and drain ports facilitate priming and draining the pump.

Application:

Specifically designed for a broad range of general applications traditionally requiring various materials such as all iron, bronzed fitted or all bronze construction. Water circulation, booster service, liquid transfer, jockey pumps, OEM applications, general water services.

Pump Dimensions & Weights

		Pump Si	ize-NPT	Α					D				Weight			
Model	HP	Suct.	Disch.	ODP	hase TEFC	3 P ODP	hase TEFC	В	С	ODP	TEFC	Е	F	G	ODP	TEFC
SCX1700-1	1/2	1-1/4"	I	13.2	14.0	13.5	14.2	2.43	6.51	5.63	6.44	4.13	4.06	4.875	29	32
SCX1700-1	3/4	1-1/4"	1	13.2	14.9	13.5	14.2	2.43	6.51	5.63	6.44	4.13	4.06	4.875	38	41
SCX1700-1	1	1-1/4"	1	14.2	15.7	14.0	15.2	2.43	6.51	5.63	6.44	4.13	4.06	4.875	47	50
SCX1700-1	1-1/2	1-1/4"	1	14.5	16.2	14.5	15.2	2.43	6.51	5.63	6.44	4.13	4.06	4.875	62	65
SCX1700-2	2	1-1/2"	1-1/4"	16.0	16.4	15.7	16.4	2.63	6.71	5.63	6.44	4.13	4.06	4.875	77	80
SCX1700-2	2-1/2	1-1/2"	1-1/4"	16.9	16.9	16.4	16.4	2.63	6.71	5.63	6.44	4.13	4.06	4.875	90	93



Note: Overload protection must be provided. Contactor with overload for I-phase or starters with heaters for 3-phase units ordered separately.

Motor	Motor		Max
Horsepower	Voltage	Phase	Amperage
1/2	115/230	- 1	8.8/4.4
	208/230/460	3	2.3/1.15
3/4	115/230	Ţ	12.2/6.1
	208/230/460	3	3.1/1.55
1	115/230	- 1	14.8/7.4
	208/230/460	3	3.6/1.8
1-1/2	115/230	- 1	19.2/9.6
	208/230/460	3	4.7/2.35
2	230	1	12
	208/230/460	3	6.8/3.4
2-1/2	230	- 1	12
	208/230/460	3	8.5/4.25

Features

Capacities:	I00 GPM
Heads:	135 Ft.TDH
Working Pressures: Max temp:	125 psig 185° F (85° C)
Direction of rotation:	Clockwise when viewed

Motors: CSA Listed NEMA 56J Frame 1/2 - 3 HP Single phase -

Voltage 115/230 VAC ODP and TEFC Three phase - Voltage 208-230/460 VAC ODP and TEFC

from the motor end

Model SCX1700 Performance Curve

